Passive Tag

Overview

RFID application is very popular in access and attendance control for convenience and security purposes. With proximity reader (sensor and standalone), access and security management is possible with proximity card and key chain. Information such as attendance, access data tracking and monitoring is stored and can be printed for analysis.

- Popular applications in access control and security purposes
- CE and FCC Certificated
- RoHS Compliant
- Tag size, color, frequency & company logo customizing options

SUZCR07N

Specification

Frequency	13.56 MHz
Read Range	3cm
Size	● 15 x 19mm (Φ x H) ● 25 x 0.67mm (Φ x H) ● 30 x 0.33mm (Φ x H)
Weight	● 0.3g for 15 Φ ● 0.6g for 25 Φ ● 0.4g for 30 Φ
Material	● PU for 15 Φ ● PET for 25 Φ ● PET for 30 Φ
Color	Glue (Customized Color Available)
Operating Temperature	-20℃～+70℃
Storage Temperature	-20℃～+90℃
Package	50 pcs per box; 1000 boxes per carton
IC Item	● Mifare S50,Mifare S70, Mifare Ultralight ● I-Code SLI, I-Code SLI-S, I-Code EPC ● Tag-it Plus, Tag-it Pro

Application

- Elevator Management
- Parking and toll collection
- Access Control System
- Contactless public phones

SECURE SMART SIMPLE