

SUZCR-M4U-039

RFID READER/WRITER FOR LF, HF, NFC, BLE



SUZCR-M4U-039

PCB bottom view



SUZCR-M4U-039

PCB bottom view

SUZCR-M4U-039 integrates RFID (125 kHz, 134.2 kHz and 13.56 MHz), NFC and Bluetooth Low Energy capabilities into a compact but powerful reader. Its reduced size combined with excellent read/write performance makes it the perfect reader for all applications where small size and full performance matters, e.g. print solutions, healthcare applications, driver identification, POS integration and much more. Furthermore, the SUZCR-M4U-039 provides access to most common host interfaces such as USB, serial (TTL) or I2C which are readily accessible through an on-board connector.

SUZCR-M4U-039 allows users to read and write almost all common worldwide 125 kHz, 134.2 kHz and 13.56 MHz tags and/or labels. It supports all major transponders from various suppliers like ATMEL, EM, ST, NXP, TI, HID etc. and ISO standards like ISO14443A/B (T=CL), ISO15693, ISO18092 / ECMA-340 (NFC).

- Special features:
 - Powerful SDK for writing Apps which are executed directly on the reader
 - Firmware update in the field possible
 - Onboard 18 kB flash storage, e.g. for storing user accessible non-volatile data
 - Direct chip-commands support
 - One onboard SAM socket (Secure Access Module)
 - CCID and PC/SC 2.01
 - 3 GPIOs
 - 3D construction data (STEP) available on request
 - supports quick centralized (re)configuration over network and over wireless interface with SUZCR-M4U-039 CONFIG Card



Elevator



EV Chargers



Access



Shop POS



Fitness Equipment



Ticket POS



PC Log-in



Document Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time Attendance



Industrial PC

● TECHNICAL DATA

FREQUENCY	125 kHz/134.2 kHz (LF) / 13.56 MHz (HF) /2402 MHz - 2480 MHz (BT)
ANTENNA	Integrated
DIMENSIONS (L X W X H)	OEM Board (compact reader): 50 mm x 35 mm x 7 mm, maximum diameter < 55 mm.
POWER SUPPLY	4.3 V - 5.5 V via USB; via connector CNB 3.3 V +/- 5%
CURRENT CONSUMPTION	RF field on: 120 mA typically + 16 mA (BT) / Sleep: 500 µA typ. / Cyclic Operation: TBD
TEMPERATURE RANGE	Operating: -25 °C up to +80 °C (-13 °F up to +176 °F) Storage: -45 °C up to +85 °C (-49 °F up to +185 °F)
RELATIVE HUMIDITY	5% to 95% non-condensing
READ- / WRITE DISTANCE	LF and HF: Up to 100 mm / 4 inch, depending on environment and transponder / BT: n/a
TRANSMISSION SPEED	Host: USB Full speed (12 Mbit/s), RS-232 up to 115.200 baud; HF Air: up to 848 kbit/s, BT Air: up to 100 kbit/s
MODES OF OPERATION	USB keyboard emulation – USB virtual COM port – CCID / PC/SC 2.01
BLUETOOTH LOW ENERGY	Bluetooth V4.1, software upgradable to V4.2; API; standards as GAP, SM, L2CAP, ATT; predefined GATT structure; up to 8 connections; AES128 supported
MTBF	500,000 hours
WEIGHT	Approx. 9 g
COMPATIBLE PIN HEADER	PTT-112-01-L-D or TMM-112-03-F-D by Samtec
SUPPORTED TRANSPONDERS (STANDARD)	<p>ISO14443A: LEGIC Advant¹⁾, MIFARE Classic 1k & 4k EV1²⁾, MIFARE Classic, MIFARE Mini, MIFARE DESFire EV1, MIFARE DESFire EV2²⁾, MIFARE Plus S, X, MIFARE Pro X³⁾, MIFARE Smart MX³⁾, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Ultralight EV1, NTAG2xx, PayPass³⁾, SLE44R35, SLE66Rxx (my-d move)³⁾, Topaz</p> <p>ISO14443B: Calypso³⁾, Calypso Innovatron protocol³⁾, CEPAS³⁾, HID iCLASS¹⁾, Moneo³⁾, Pico Pass⁴⁾, SRI4K, SRX4K, SRI512, SRT512</p> <p>ISO18092 ECMA-340: NFC Forum Tag 1-5, NFC Peer-to-Peer, Sony FeliCa⁵⁾, NFC Active and passive communication mode</p>

	<p>ISO15693: EM4x33³⁾, EM4x35³⁾, HID iCLASS¹⁾, HID iCLASS SE/SR¹⁾, ICODE SLI, LEGIC Advant¹⁾, M24LR16/64, MB89R118/119, SRF55Vxx (my-d vicinity)³⁾, Tag-it, PicoPass⁴⁾</p> <p>125 kHz, 134.2 kHz: AWID, Cardax, CASI-RUSCO, Deister⁶⁾, EM4100, 4102, 4200⁷⁾, EM4050, 4150, 4450, 4550, EM4305⁸⁾, FDX-B, EM4105, HITAG 1⁹⁾, HITAG 2⁹⁾, HITAG S⁹⁾, ICT⁸⁾, IDTECK, Isonas⁸⁾, Keri, Miro, Nedap⁶⁾, PAC, Pyramid, Q5, T5557, T5567, T5577, TIRIS/HDX, TITAN (EM4050), UNIQUE, ZODIAC</p>						
SUPPORTED TRANSPONDERS (VERSION P)	All Standard Transponder, Cotag, G-Prox ⁶⁾ , HID DuoProx II, HID ISO Prox II, HID Micro Prox, HID ProxKey III, HID Prox, HID Prox II, Indala, ioProx, Nexwatch						
SUPPORTED TRANSPONDERS (VERSION PI)	Requires external TWN4 SIO Card, All Standard Transponder, All Version P Transponder, HID iCLASS ¹⁰⁾ , HID iCLASS SE/SR/SEOS(CSN and Facility Code/PAC) ¹⁰⁾ , HID iCLASS Elite & SE Elite						
PERIPHERAL INTERFACES	USB, RS232, TTL serial (logic level 3.3 V, CMOS, 5 V tolerant), I ² C, SPI, 3 GPIOs, CAN ⁸⁾ , Clock/Data, Wiegand, 1-Wire ⁸⁾						
OS SUPPORT	Windows XP, Vista, Embedded CE ⁸⁾ , 7 (32-/64-bit), 8, 8.1, 10, Linux, Android ⁸⁾ , iOS ⁸⁾ , MAC OS X ⁸⁾						
CERTIFICATIONS	RoHS-II compliant, CE/RED, FCC Single Modular Approval, IC, ACA						
ORDER CODE(S)	<table border="0"> <tr> <td>T430-F7C0</td> <td>OEM Board Wiegand</td> </tr> <tr> <td>T430-F7C0-P</td> <td>OEM Board Wiegand Version P</td> </tr> <tr> <td>T430-F7C0-PI</td> <td>OEM Board Wiegand Version PI</td> </tr> </table>	T430-F7C0	OEM Board Wiegand	T430-F7C0-P	OEM Board Wiegand Version P	T430-F7C0-PI	OEM Board Wiegand Version PI
T430-F7C0	OEM Board Wiegand						
T430-F7C0-P	OEM Board Wiegand Version P						
T430-F7C0-PI	OEM Board Wiegand Version PI						
<p>¹⁾UID Only ²⁾r/w enhanced security features on request ³⁾r/w in direct chip command mode ⁴⁾UID Only, read/write on request ⁵⁾UID + r/w public area ⁶⁾Hashvalue only ⁷⁾Only emulation of 4100, 4102 ⁸⁾On request ⁹⁾Without encryption ¹⁰⁾UID + PAC (CSN & Facility Code), r/w on request</p>							

● CONNECTOR ASSIGNMENT

	X2		
RESET	24	23	PWRDWN-
GPIO6	22	21	GPIO5
GPIO4	20	19	VCC
COM1_RX	18	17	COM1_TX
USB_DP_P	16	15	UGND
USB_DM_P	14	+13	UVCC
GND	12	11	V24_RXD
HOSTSENSE	10	9	V24_TXD
SPI_SCK	8	7	SPI_SS-
SPI_MISO	6	5	SPI_MOSI
I2C_SDA	4	3	I2C_SCI
CAN_RX	2	1	CAN_TX